

	С	ONFOR	MITY CE	ERTIFICA	ATE .		
Ground Granulated Blastfurnace Slag Pro				oduced at	Scunt	horpe	Works
				ole Period	Januar	y 2020	
Certificate of Conformity of GGBS to EN 15167-1:2006				Certificate of Conformity of Combinations of GGBS and CEM I Portland Cement to			
Spot samples of GGBS were taken and tested to determine conformity to the autocontrol requirements of EN 15167-1:2006 "Ground granulated blastfurnace slag for use in concrete, mortar and grout" following the methods given in that standard. The values			Annex A of BS 8500-2:2015  Portland Cement Source:  N/A				
reported are mean values for the monthly production period.				For combinations of GGBS supplied from the above			
Scunthorpe GGBS Only				works with the above CEM I Portland cement the permitted			
Results		Product	EN Limit	proportions conforming to the requirements given in		s given in	
Fineness m <sup>2</sup> /kg		521	min. 275	annex A of BS 8500-2:2015 are:			
Magnesium Oxide MgO %		8	max. 18	S	Strength	Not Less	Not More
Sulfate SO <sub>3</sub> %		0.2	max. 2.5		Class	Than**	Than**
Sulfide S <sup>2-</sup> %		0.8	max. 2.0		52.5L	N/A	N/A
Chloride Content Cl <sup>-</sup> %		0.03	max. 0.10		42.5L	N/A	N/A
Moisture Content %		0.0	max. 1.0		32.5L	N/A	N/A
Corrected Loss on Ignition %		1.0	max. 3.0				
Aluminium Oxide Al <sub>2</sub> O <sub>3</sub> %		12.6	to 1 d.p.	Conformity Evaluation Period (if less than 6 months)		N/A	month(s)
Note: If the value of Al <sub>2</sub> O <sub>3</sub> is ≥ 14.5% the '+SR' re		triction will					
be exceeded if the $C_3A$ of the CEM I is >10%.				Combinat	tion Designation		
Alkalis as Na 2 O equ. (acid soluble)			(Table 1 BS 8500-2:2015)				
Guaranteed Alkali limit %		≤ 1.0			CIIA-S	6	20
Certified Average Alkali ( Last 25 ) %		0.62			CIIB-S	21	35
Declared Mean: Mean last 25 + (SD last 25 x 1.64) %		0.70			CIIIA	36	65
COMBINATION OF 50% LAN CEM I PORTLAND CEMEN			CIIIB 66 80  ** % GGBS		GGBS 80		
Initial Setting Time min.		220	not > than 2 x PC	Results of tests in accordance with BS EN 196-1 for 50% GGBS combination with 50% CEM I Portland cement shown above			
Activity Index %	7 days	72	min. 45	COMBINA	combination with 50% CEW I Portland cement shown above		
-	28 days	94	min. 70		Age	7 Days	28 Days
LABORATORY STOCK CEM I PO	RTLAND C	EMENT ON	LY	Compressiv	e Strength N/mm <sup>2</sup>	N/A	N/A
The stock CEM I Portland cement used in these tests was supplied by Hanson Ribblesdale works and the following results were obtained from that sample				The samples of LKAB Minerals GGBS and the CEM I Portland cement were bulk average monthly samples for the works specified			
Initial Setting Time min		180					
	7 days	46.6					
Compressive Strength N/mm <sup>2</sup>	28 days	56.2					
The GGBS contained no additional materials other than those permitted. The above results and other tests demonstrate the conformity of the material sold during the month to the requirements of EN 15167-1:2006					1333-0	PR-00194	

Signed:

6. Furtett